

TRACT 37 IN TOWNSHIP 3 NORTH, RANGE 24 EAST SECTION 5 AND TRACTS 37 AND 38 IN TOWNSHIP 4 NORTH, RANGE 24 EAST IN UNSURVEYED SECTION 32, MT. DIABLO MERIDIAN, MONO COUNTY, CALIFORNIA

RECORD OF SURVEY NO: 32-94

CAP STAMPED	MONUMENT DESCRIPTION	ACCESSORY DESCRIPTION	CAP STAMPED	MONUMENT DESCRIPTION	ACCESSORY DESCRIPTION
	AT THE INTERSECTION OF THE ORDINARY HIGH WATER MARK (OHWM) OF LOWER TWIN LAKE AND WITH THE NORTH TOWNSHIP LINE OF T.3N, R.24E., ON THE LINE BETW. THE N. 1/4 COR. OF SEC. 5 AND THE MEANDER COR. FOR SEC. 4, BOTH IN T.3N, R.24E., SET A STANDARD U.S. FOREST SERVICE ALUMINUM POST, 30 INS. LONG, 2-1/2 INS. DIAM., 20 INS. INTO THE GROUND, OVER A PLASTIC-ENCASED MAGNET WITH AN ALUMINUM CAP MKD. AS SHOWN. BUILT MOUND OF STONE AROUND MONUMENT, 1 FT. DIAM., BASE TO TOP, UNABLE TO FIND THE MONUMENT SET BY RONALD L. MCCORMICK IN 1977 EVEN THOUGH RECOVERED BY DAVID L. DUKLETH IN 1994. SEARCHED DILIGENTLY FOR IT AT THE CALCULATED LOCATION AFTER LAKE LEVEL HAD RECEDED.	NEW ACCESSORIES FOR ANGLE POINT 1, TR37, T.3N, R.24E., SEC. 5. FROM WHICH, A REBAR, 1/2 IN. DIAM., 2 FT. LONG, DRIVEN 3 INS. BELOW GROUND ON THE NORTHERLY SIDE OF A 10 FT. WIDE WALKING TRAIL ABOVE THE OHWM OF LOWER TWIN LAKE, BEARS N. 3° E., 37.9 FT. DIST. A BOLT, 1.7 FT. LONG, 1/2 IN. DIAM., THE BOTTOM OF WHICH IS A ROUNDED POINT AND IS THREADED FOR 0.475 FT. UP FROM BOTTOM WITH THE TOP OF THE BOLT BEING A SQUARE BOLT HEAD, 3/4 IN. X 3/4 IN., DRIVEN 0.3 FT. BELOW GROUND ALONG THE LITTER LINE AND 7 FT. +/- BELOW THE VEGETATION LINE AT THE OHWM, BEARS S. 31°35'30" W., 16.6 FT. DIST.		AS PER BLM FIELD NOTES APPROVED IN 1981: NORTH ON LINE 9-10, TRACT 37, SEC. 5. AT 0.50 CHS., DIRT ROAD, 15 LKS. WIDE, BEARS E. AND W. AND N. 50° W. USING THE RECORD BEARING OF NORTH FROM AP 9 TO AP 10 AS SHOWN ON THE PLAT AND IN THE FIELD NOTES OF THE SURVEY EXECUTED BY RONALD L. MCCORMICK IN 1977, SET A STANDARD U.S. MONUMENT, 30 INS. LONG, 2-1/2 INS. DIAM., IN THE TOP OF A STEEP EMBANKMENT AS DESCRIBED IN THE APPROVED FIELD NOTES FROM THE 1977 BLM SURVEY, PROJECTING 2 INS. ABOVE GROUND. THERE HAS BEEN A SIGNIFICANT AMOUNT OF EROSION IN THE PAST 37 YEARS IN THE STEEP EMBANKMENT AREA NEAR THIS WC TO AP 10 AND THE SMC. MCCORMICK HAD SET HIS CORNER IN 1977 FOR BLM FARTHER TO THE NORTH WHICH IS NOW BEACH SAND NORTH OF THE STEEP EMBANKMENT AREA.	NEW ACCESSORIES FOR THE WC TO AP 10 AND SMC IN TR37, T.3N, R.24E., SEC. 5. FROM WHICH, A BOULDER, 3 FT. X 2 FT. X 2 FT., BEARS S. 22° W., 27.6 FT. DIST., MKD. X80. AN EXPOSED SECTION OF LEDGEROCK, MEASURING 18 INS. X 18 INS. AND PROJECTING 1 IN. ABOVE THE SURFACE OF THE GROUND, WITH A DRILL HOLE, 3/4 IN. DIAM. AND 1/2 IN. DEEP, BEARS S. 89° W., 15.8 FT. DIST. LEDGEROCK IS ON A SMALL TRAIL THAT LEADS INTO A STAND OF ASPEN ALONG THE TOP OF A STEEP EMBANKMENT ABOVE LOWER TWIN LAKE. AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER AND PROPERTY BOUNDARY SIGNS ATTACHED, IS DRIVEN NEXT TO COR. POSTED NATIONAL FOREST BOUNDARY LINE SOUTH OF CORNER ALONG A ROAD NAMED ASPEN LANE IN TWIN LAKES SUBDIVISION. MONUMENT WAS SET OVER A PLASTIC-ENCASED MAGNET SURROUNDED BY A COLLAR OF STONE, 1 FT. DIAM.
	FOUND THIS BLM MONUMENT 1 IN. BELOW GROUND NEXT TO A LATHE WITH ITS TOP PAINTED ORANGE. DROVE A BROWN CARSONITE POST WITH LAND SURVEY MARKER DECAL ATTACHED NEXT TO COR. FOR THIS RECOVERED BLM MONUMENT THAT WAS ORIGINALLY DESCRIBED AS THE S. 1/4 COR. FOR S32 ONLY IN T.4N, R.24E., AND AP2 TR37 IN T.3N, R.24E., IN WHICH BLM STATED IN THEIR FIELD NOTES THAT THEY REMOVED THE 1/4 S32 OFF THE CAP AND ADDED THE NEW TRACT NUMBERS AND THE DATE 1994 TO THE CAP. THIS DID NOT OCCUR IN THE FIELD. THIS SURVEY MARKED THE CAP CORRECTLY AS SHOWN. BASED OFF MCCORMICK'S PLAT AND THE AFFIDAVIT BY WALTER G. REID, AP 2 OF TRACT 37, T.3N, R.24E., IS THE N. 1/4 CORNER FOR SEC. 5. IT CANNOT ALSO BE THE S. 1/4 COR. OF SEC. 32 BECAUSE THAT SECTION IS UNSURVEYED.	RECORD ACCESSORIES FOR ANGLE POINT 2, TR37, T.3N, R.24E., S5, FOUND THE WALTER G. REID MONUMENT ON THE N. SIDE OF THE TWIN LAKES HWY., TAKEN BY DAVID L. DUKLETH IN 1994, A BRASS DISK, 1-1/2 IN. DIAM., MARKED CE 7522, FIRMLY SET FLUSH IN THE TOP OF A CONCRETE CYLINDER, 6 INS. DIAM., 20 INS. BELOW GROUND, BEARS N. 10° 18' 48" E., 3.911 CHS., (RECORD N. 10° 19' E., 3.915 CHS.), FOR A HIGHWAY RIGHT OF WAY MONUMENT ON THE NORTH SIDE OF TWIN LAKES HIGHWAY. PLACED A PLASTIC-ENCASED MAGNET OVER THE EXPOSED BRASS CAP TO AID IN FUTURE RECOVERY. DROVE A BROWN CARSONITE POST WITH LAND SURVEY MARKER DECAL ATTACHED NEXT TO COR. AND FACING HWY. AN OLD LATHE WAS NEXT TO COR. CENTER OF CONCRETE RECTANGULAR BOX, MEASURING 1.7 X 3.2 FT., WHICH HAS TWO WATER VALVES INSIDE BOX, BEARS N. 83°41' E., 46.8 LKS. DIST. (RECORD IS CONCRETE BLOCK BOX, 2 FT. X 2 FT., BEARS N. 86° E., 49 LKS. DIST.), AS STATED IN THE FIELD NOTES, ALSO BEING THE NW COR. OF PARCEL 3, LOT 3, TWIN LAKES SUBDIVISION. CENTER OF CONCRETE RECTANGULAR BOX, MEASURING 1.6 X 1.35 FT., WHICH HAS ONE WATER VALVE INSIDE IT, BEARS N. 83°43' E., 34.4 FT. DIST. A REPLACEMENT POWER POLE BEARS EAST, 54 LKS. DIST., MATCHING WHERE THE ORIG. POWER POLE WAS THAT HAD THE NAIL IN IT THAT BLM HAD MEASURED TO.		FOUND BLM IRON POST MON. AS DESCRIBED IN THE FIELD NOTES EXCEPT THERE WAS NO MOUND OF STONE. IRON POST HAD ACCUMULATED RUST SUCH AS WHEN SOMETHING WOULD BE UNDER WATER FOR SOME TIME THEN EXPOSED. BLM STATED IN THEIR FIELD NOTES THAT THEY REMOVED THE S33 REFERENCE AND ADDED THE DATE 1994 TO THE CAP. THIS DID NOT OCCUR IN THE FIELD. THIS SURVEY REMOVED THE S33 REFERENCE AND ADDED THE DATE 2013 TO THE CAP. USED THIS CORNER ALONG WITH THE N. 1/4 COR. OF SEC. 5 TO SET A WITNESS COR. TO THE MC ON THE OTHER SIDE OF THE LAKE TO THE WEST AND FOR ANGLE POINT 1, TRACT 37 IN T.3N, R.24 E., IN SECTION 5. WHERE BLM CHISELED THE X80 IS 4-1/2 FT. ABOVE MON. THE TOP OF THE ROCK WHERE THE X80 IS CHISELED IS 6-1/2 FT. ABOVE MON.	RECORD ACCESSORY FOR THE MC FOR SEC. 4 FROM WHICH, A GRANITE BOULDER, 12 FT. X 5 FT. X 6.5 FT. HIGH, MKD. X80 ON NNW FACE, 4-1/2 FT. ABOVE MONUMENT, (RECORD 6-1/2 FT.), WITH THE X BEARING S. 48°25' E., 7.7 LKS. DIST., (RECORD S. 40° E., 8 LKS.). LETTERS ON NNW FACE WERE BARELY DISCERNABLE SO THIS SURVEY REPERISHED THEM WITH A CHISEL TO FRESHEN UP THOSE LETTERS. PAINTED THE EXPOSED PIPE RED WHERE THE RUST HAD BUILT UP, AND BUILT A MOUND OF STONE, 2 FT. DIAM., AROUND MONUMENT. FROM WHICH A NEW ACCESSORY, A GRANITE BOULDER, 8 FT. X 4 FT. X 3 FT. HIGH, MKD. X80 ON THE WEST FACE, WITH THE X BEARING N. 49°58' E., 22.3 FT. DIST.
	FOUND A BLM IRON POST, 2 INS. DIAM., PROJECTING 2 INS. ABOVE GROUND, SURROUNDED BY A MOUND OF STONE, 3 FT. DIAM., BASE TO TOP. AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER SIGN ATTACHED, WAS FOUND NEXT TO COR. BLM DID NOT MARK THE CAP AS STATED IN THE FIELD NOTES. THEY DID NOT REMOVE THE MARKS S32 AND ADD THE NEW TRACT NUMBER AND DATE 1994 TO THE CAP. THIS SURVEY REMOVED THE MARKS S32 AND ADDED THE NEW TRACT NUMBER AND THE DATE 2013 TO THE CAP. THE POWER POLE ACCESSORY ESTABLISHED IN 1977 HAS BEEN REMOVED AS WAS STATED IN THE FIELD NOTES. NATIONAL FOREST BOUNDARY LINE IS POSTED NORTH AND SOUTH OF CORNER.	RECORD ACCESSORY FOR ANGLE POINT 3, TR37, T.3N, R.24E., S5. THIS COR. ALSO SERVES AS ANGLE POINT 3, TR38, IN T.4N, R.24E., IN UNSURVEYED SEC. 32 AND IS THE W. 1/16 COR. FOR SEC. 5 ONLY ON THAT SECTION'S NORTH LINE. FROM WHICH, A JEFFREY PINE, NOW 35 INS. DIAM., BEARS S. 81° W., 1.36 CHS. DIST., (RECORD 135 LKS.), MKD. WITH A HEALED BLAZE, PAINTED BT BLAZE RED WHICH WAS BELOW EXISTING BLM BT TAG ON TREE FACING COR. PAINTED RED RING AROUND TREE ABOVE BLM BT TAG. AN IRON STAKE, 1 IN. DIAM., PROJECTING 12 INS. ABOVE GROUND AND LEANING UPHILL, LOCATED AT BASE WHICH BEARS N. 27° W., 4.4 FT. DIST. TOP OF STAKE HAS A 1 IN. X 2 IN. RECTANGULAR FLANGE ON IT.		POINT FOR SPECIAL MEANDER CORNER AND ANGLE POINT 1, TRACT 37 IS DETERMINED AT INTERSECTION WITH THE RECORD MEANDERS OF LOWER TWIN LAKE, AND RECORD BEARING FROM THE EASTERLY RECOVERED LOCAL MONUMENT ON THE NORTH BOUNDARY FOR TWIN LAKES SUBDIVISION MAP BOOK 1, PAGE 52, MONO COUNTY RECORDS, FOUND A STAINLESS STEEL POST, 2-1/2 INS. DIAM., RISING 10 INS. ABOVE GROUND IN A SCATTERED MOUND OF STONE. SMC IS LOCATED AT EDGE OF CUT BANK, BEARS N. AND S. DROVE AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER AND PROPERTY BOUNDARY SIGNS ATTACHED, NEXT TO COR. POSTED NATIONAL FOREST BOUNDARY LINE WEST OF COR. BLM REPORTED THE CAP MARKINGS WRONG IN THE FIELD NOTES BUT CORRECTLY MKD. IT IN THE FIELD, ON THE TWIN LAKES SUBDIVISION PLAN, NORTH PORTION, LOT 3, BLOCK N, PARCEL 1; THE MONUMENT SET BY WALTER G. REID MARKS THE NE COR. OF PARCEL 1 AND WESTERLY LINE OF CHARLEY DAY DRIVE.	ACCESSORIES FOR AP 1 IN TRACT 37, T.4N, R.24E. AND THE SMC. FROM WHICH, AN ASPEN, 10 INS. DIAM., BEARS N. 78° W., 7.7 FT. DIST., MKD., WITH A BARK-SCRIBED A BRASS DISK, 1-1/2 IN. DIAM., FIRMLY SET, MKD. CE 7522, SET FLUSH IN TOP OF CONCRETE BLOCK, 6 INS. SQ., 11 INS. BELOW GROUND SURFACE, BEARS N. 89°57'46" W., (RECORD N. 89°59'39" W. BY BLM), 1.581 CHS. DIST., RECORDED IN MAP BOOK 1, PAGE 52, MONO COUNTY RECORDS, A 1/2 IN. REBAR, WHICH MARKS THE NW CORNER OF PARCEL 1 IN BLOCK N, AND THE EASTERLY R-O-W OF TWIN LAKES HIGHWAY AS SHOWN ON THE SUBDIVISION PLAT, BEARS N. 89°59'33" W., 107.7 FT. DIST., (RECORD WEST ON SUB. PLAT), REBUILT MOUND OF STONE, 2 FT. DIAM., BASE TO TOP, PAINTED XBT AND RING AROUND TREE RED. THE DIST. BETW. THESE 2 MONS. WAS 3.35 FT., (RECORD 3.29 FT.).
	FOUND THE BLM IRON POST SET IN 1977 DISTURBED AND OUT OF POSITION LAYING HORIZONTAL ON THE TOP OF BANK COVERED IN DIRT AND PINE NEEDLE LITTER, FOUND ROCK AT WATER LINE WHERE BLM SET THE COR. IN 1977. ON THE LINE BETW. AP 3 AND AP 6, GOING SOUTHERLY FROM AP 3 AND INTERSECTING THE NORTH SHORE OF UPPER TWIN LAKE, SET A STANDARD 30 IN. LONG USFS ALUMINUM POST, 22 INS. IN THE GROUND, OVER A PLASTIC-ENCASED MAGNET, SURROUNDED BY A MOUND OF STONE, 2 FT. DIAM., BASE TO TOP, BURIED DISTURBED BLM POST NEXT TO CORNER. DROVE AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER AND PROPERTY BOUNDARY SIGNS ATTACHED, NEXT TO CORNER. POSTED NATIONAL FOREST BOUNDARY LINE NORTH OF COR. FROM AP 3 TO THE WEST EDGE OF THE BOULDER WHERE BLM SET THIS COR. IN 1977 MATCHES THE RECORD DIST. 8.79 CHS. EXACTLY.	NEW ACCESSORIES FOR ANGLE POINT 4, TR37, T.3N, R.24E., SEC. 5. FROM WHICH, A LARGE GRANITE BOULDER, MEASURING 16 FT. X 12 FT. X 12 FT. HIGH, WITH A DRILL HOLE, 3/4 IN. DIAM. AND 1/2 IN. DEEP, BEARS N. 66° 47' 39" E., 138.1 FT. DIST. A BOULDER, MEASURING 4 FT. X 4 FT. X 3 FT. HIGH, BEING THE SAME BOULDER WHERE BLM HAD SET THE COR. IN 1977 ON ITS WEST EDGE AS STATED IN THE FIELD NOTES, NOW MKD. WITH AN X80, OF WHICH THE X BEARS S. 24° 14' 40" E., 9.9 FT. DIST. A BOULDER, MEASURING 4 FT. X 3 FT. X 3 FT. HIGH, IN THE WATER ON THE NORTH SHORE OF UPPER TWIN LAKE, MKD. WITH A DRILL HOLE, 3/4 IN. DIAM., 1/2 IN. DEEP, BEARS S. 59° 14' 44" W., 27.0 FT. DIST. A JEFFREY PINE, 21 INS. DIAM., BEARS N. 76° W., 19.2 FT. DIST., MKD. XBT AT BASE. NAILED BT TAG ON TREE FACING COR. PAINTED BLAZE RED.		POINT FOR ANGLE POINT NO. 2 OF TRACT 37, IDENTICAL WITH ANGLE POINT NO. 1 OF TRACT 38, WAS DETERMINED AT RECORD BEARING AND DISTANCE FROM THE MOST WESTERLY RECOVERED LOCAL MONUMENT ON THE NORTH BOUNDARY FOR TWIN LAKES SUBDIVISION, MAP 1, PAGE 52, MONO COUNTY RECORDS. FOUND A STAINLESS STEEL POST, 2-1/2 INS. DIAM., PROJECTING 3 INS. ABOVE GROUND, AND IN A COLLAR OF STONE, 3 FT. DIAM., BASE TO TOP. BLM DID NOT PUT THE ANGLE POINT NUMBERS ON THE CAP. THIS SURVEY ADDED THE ANGLE POINT NUMBERS AND THE DATE 2012 TO THE CAP. THE CORNER WAS OVERGROWN WITH SAGEBRUSH. DROVE AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER AND PROPERTY BOUNDARY SIGNS ATTACHED, NEXT TO CORNER. PAINTED EXPOSED PIPE AND COLLAR OF STONE RED. UNABLE TO RECOVER THE ONE ORIG. ACCESSORY, AN IRON ROD, 3/8 IN. DIAM., FIRMLY SET, PROJECTING 1/2 IN. FROM TOP OF CONCRETE BLOCK, 6 INS. SQ., 8 INS. BELOW SURFACE OF GROUND, BEARS S. 89°59'39" E., 3.145 CHS. DIST., AS RECOVERED BY BLM IN 1994. THIS IRON ROD WAS USED IN THE CALCULATION TO PUT THIS TRACT COR. IN. THIS AREA HAS HAD REPEATED MUDFLOWS AND THE COR. WAS NOT DETECTABLE.	THERE WERE NO RECORD ACCESSORIES FOR THIS COR. FROM WHICH A NEW ACCESSORY, A JEFFREY PINE, 22 INS. DIAM., BEARS N. 48° E., 61.3 FT. DIST., MKD. XBT. PAINTED XBT IN BLAZE AND RING AROUND TREE ABOVE BT TAG RED. NATIONAL FOREST BOUNDARY LINE POSTED EAST AND WEST OF COR.
	BLM SET A COR. IN 1977 ON THIS SOUTH SIDE OF UPPER TWIN LAKE BUT WAS UNABLE TO LOCATE IT. THE CALCULATED POSITION FROM THE BLM FIELD NOTES AND PLAT HAD THE POSITION IN THE WATER. UPPER TWIN LAKE HAS RISEN SINCE THE DAM WAS CONSTRUCTED ON THE LOWER NORTHEAST END OF TWIN LAKE SO THE MONUMENT WAS LIKELY KNOCKED OUT OF POSITION DUE TO THE ACTION OF WATER AND/OR THE MOVEMENT OF ICE. ON THE LINE BETW. AP 6 TO AP 3, AND PROCEEDING NORTHERLY FROM AP 6 TO THE INTERSECTION WITH THE SOUTH SHORE OF UPPER TWIN LAKE, SET A STANDARD USFS ALUMINUM POST, 30 INS. LONG, ON THE TOP OF BANK ABOVE THE SOUTH SHORE OF UPPER TWIN LAKE, 22 INS. IN THE GROUND, OVER A PLASTIC-ENCASED MAGNET, AND SURROUNDED BY A MOUND OF STONE, 1 FT. DIAM., BASE TO TOP. NATIONAL FOREST BOUNDARY LINE POSTED SOUTH OF COR.	NEW ACCESSORIES FOR ANGLE POINT 5, TR37, T.3N, R.24E., SEC. 5. FROM WHICH, A BOULDER, MEASURING 6 FT. X 4 FT. X 6 FT. HIGH, IN THE WATER ON THE SOUTH SHORE OF UPPER TWIN LAKE, BEARS S. 78° 11' 42" W., 42.6 FT. DIST., MKD. X80 ON THE TOP OF THE BOULDER. A SPIKE DRIVEN IN AN OLD STUMP ON THE SHORELINE, PRESUMABLY LEFT BY THE BLM SURVEY CREW IN 1977, BEARS N. 1° W., 36.6 FT. DIST. DROVE AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER AND PROPERTY BOUNDARY SIGNS ATTACHED, NEXT TO CORNER.		AS PER BLM FIELD NOTES, POINT FOR ANGLE POINT 2, TRACT 38, WAS DETERMINED AT RECORD 20 CHS. NORTH OF THE W. 1/16 SEC. COR. OF SECS. 5 AND 32. FOUND A STAINLESS STEEL POST, 2-1/2 INS. DIAM., PROJECTING 10 INS. ABOVE GROUND. THERE WAS NO MOUND OF STONE. BLM DID NOT MARK AP2 ON THE CAP AS STATED IN THE FIELD NOTES. THIS SURVEY ADDED AP2 AND 2012 TO CAP. BUILT MOUND OF STONE, 2 FT. DIAM., BASE TO TOP, AROUND COR. DROVE AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER AND PROPERTY BOUNDARY SIGNS ATTACHED, NEXT TO COR. NATIONAL FOREST BOUNDARY LINE IS POSTED EAST AND SOUTH OF CORNER.	THERE WERE NO RECORD ACCESSORIES FOR THIS COR. FROM WHICH A NEW ACCESSORY: A REBAR, 1/2 IN. DIAM., 16 INS. LONG, DRIVEN 6 INS. BELOW GROUND DIRECTLY UPHILL OF MON., BEARS N. 35° 29' W., 3.1 FT. DIST. BUILT A MOUND OF STONE, 1 FT. DIAM., OVER TOP OF REBAR. PAINTED EXPOSED BLM STEEL POST AND ITS 2 FT. DIAM. MOUND OF STONE RED.
	FOUND A BLM IRON POST AND BRASS CAP AS MKD. PROJECTING 10 INS. OUT OF THE GROUND, SURROUNDED BY A MOUND OF STONE, 1 FT. DIAM., BASE TO TOP. COR. IS LOCATED ON A STEEP NW SLOPE. A STEEL SIGNPOST, WITH ATTENTION SIGN ATTACHED, WAS FOUND DRIVEN UPHILL SEVERAL FEET ABOVE COR. DROVE AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER AND PROPERTY BOUNDARY SIGNS ATTACHED, 5 FT. EAST OF COR. ON LINE. POSTED NATIONAL FOREST BOUNDARY LINE NORTH AND EAST OF CORNER.	THERE ARE NO RECORD ACCESSORIES FOR ANGLE POINT 6. FROM WHICH A NEW ACCESSORY, A REBAR, 1/2 IN. DIAM., 16 INS. LONG, 4 INS. BELOW GROUND UPHILL FROM MONUMENT, BEARS S. 27°32' E., 5.3 FT. DIST. PAINTED EXPOSED PIPE AND MOUND OF STONE RED.		THE COR. OF SECS. 5, 6, 31, AND 32, MONUMENTED WITH AN IRON POST, 1 IN. DIAM., LOOSELY SET, IN A SCATTERED MOUND OF STONE, PROJECTING 10 INS. ABOVE GROUND, WITH BRASS CAP MKD. THIS COR. WAS REESTABLISHED AND REMONUMENTED IN 1934 BY DUPREE R. AVERILL UNDER GROUP 270, FROM THE REMAINS OF THE ORIGINAL 1882 BEARING TREES: A FALLEN PINE, 40 INS. DIAM., BEARS N. 66° E., 148 LKS., WITH NO MARKS. (RECORD N. 70° E.). A FALLEN PINE, 36 INS. DIAM., BEARS S. 40° W., 82 LKS. DIST., WITH NO MARKS. FOUND MONUMENT BURIED UNDER 3 INS. OF DECOMPOSED GRANITE. REMAINS OF MOUND OF STONE HAD ROLLED DOWN THE HILL. DROVE AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER SIGN ATTACHED, NEXT TO COR. REBUILT MOUND OF STONE, 3 FT. DIAM., AROUND MON. AND SIGNPOST. PAINTED EXPOSED PIPE AND MOUND OF STONE RED. SIGNPOST IS VISIBLE FROM TWIN LAKES HIGHWAY. MCCORMICK JUST ADDED 77 TO THE BRASS CAP INSTEAD OF 1977 AS STATED IN THE FIELD NOTES. FOUND STUMPS WHERE THE TWO ORIG. BT'S WERE, NOW FILLED IN WITH DECOMPOSED GRANITE. NAILED BT TAGS TO BOTH TREES.	FROM WHICH THE 1934 BEARING TREES: A JEFFREY PINE, NOW 50 INS. DIAM., BEARS N. 3-1/2° E., 215 LKS. DIST., MKD. WITH A PARTIALLY OPEN BLAZE WITH ALL THE LETTERS AND NUMBERS VISIBLE EXCEPT THE T AND THE R. THE SCRIBING SEEN WAS 3N 24E S32 BT. BLM BT TAG WAS HANGING UPSIDE DOWN SO FIXED IT WITH TWO ADDITIONAL NAILS. PAINTED BT BLAZE RED. TREE SHOULD HAVE HAD SCRIBING 4N, NOT 3N. A JEFFREY PINE, NOW 40 INS. DIAM., BEARS S. 75° W., 124 LKS. DIST., MKD. WITH A HEALED BLAZE AND A BLM BT TAG FACING COR. PAINTED BT BLAZE RED. A JEFFREY PINE, NOW 42 INS. DIAM., BEARS N. 41-1/2° W., 250 LKS. DIST., MKD. WITH A MOSTLY PITCHED-OVER BLAZE. REMOVED MOST OF THE PITCH AND UNCOVERED ALL THE ORIG. SCRIBING EXCEPT THE T WHERE THE BLAZE HAD HEALED OVER IT. THE SCRIBING SEEN WAS 4N R24E S31 BT. BLM BT TAG WAS HANGING UPSIDE DOWN SO FIXED IT WITH TWO ADDITIONAL NAILS. PAINTED BT BLAZE RED.
	FOUND A BLM IRON POST AND BRASS CAP AS MKD., PROJECTING 10 INS. OUT OF THE GROUND, SURROUNDED BY A MOUND OF STONE, 3.5 FT. DIAM., BASE TO TOP. COR. IS LOCATED ON A STEEP NW SLOPE. AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER AND PROPERTY BOUNDARY SIGNS ATTACHED, WAS DRIVEN NEXT TO COR. POSTED NATIONAL FOREST BOUNDARY LINE NORTH AND WEST OF CORNER. PAINTED MOUND OF STONE, EXPOSED PIPE, AND EXISTING STEEL SIGNPOST WITH ATTENTION SIGN RED.	THERE ARE NO RECORD ACCESSORIES FOR ANGLE POINT 7. FROM WHICH A NEW ACCESSORY, A REBAR, 1/2 IN. DIAM., 16 INS. LONG, 3 INS. BELOW GROUND UPHILL FROM MONUMENT, BEARS S. 17°31' E., 3.1 FT. DIST. PAINTED A SOLID RED CIRCLE, 4 INS. DIAM., ON ROCK BEHIND REBAR. PAINTED EXPOSED PIPE AND MOUND OF STONE RED.		FOUND MONUMENT BURIED UNDER 3 INS. OF DECOMPOSED GRANITE. REMAINS OF MOUND OF STONE HAD ROLLED DOWN THE HILL. DROVE AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER SIGN ATTACHED, NEXT TO COR. REBUILT MOUND OF STONE, 3 FT. DIAM., AROUND MON. AND SIGNPOST. PAINTED EXPOSED PIPE AND MOUND OF STONE RED. SIGNPOST IS VISIBLE FROM TWIN LAKES HIGHWAY. MCCORMICK JUST ADDED 77 TO THE BRASS CAP INSTEAD OF 1977 AS STATED IN THE FIELD NOTES. FOUND STUMPS WHERE THE TWO ORIG. BT'S WERE, NOW FILLED IN WITH DECOMPOSED GRANITE. NAILED BT TAGS TO BOTH TREES.	FROM WHICH A NEW ACCESSORY: A GRANITE BOULDER, 8 FT. X 6 FT. X 6 FT. ON A STEEP SOUTH FACING HILL, MKD. WITH AN X80 ON TOP OF THE BOULDER, WITH THE X BEARING N. 76° E., 52.6 FT. DIST.
	FOUND A BLM IRON POST, 2-1/2 INS. DIAM., 1 FT. BELOW GROUND, ON THE EAST EDGE OF THE TRAVELLED WAY DRIVE MONUMENT IS A CHAIN NORTH OF SIGN FOR BY DAY DRIVE AND PARKER DRIVE AND THE DIRECTIONAL SIGN FOR HUNNEWELL DRIVE. PARKER DRIVE HAS A NORTHERLY AND SOUTHERLY ENTRANCE INTO IT FROM BY DAY DRIVE. PARKER DRIVE STARTS ON PRIVATE LAND BUT GOES ONTO NATIONAL FOREST. THEN GETS BACK ON PRIVATE BURIED PLASTIC-ENCASED MAGNET NEXT TO BURIED REBAR JUST UNDER THE BRASS CAP. SET TWO ALUMINUM SIGNPOSTS WITH LAND SURVEY MARKER AND PROPERTY BOUNDARY SIGNS ATTACHED EAST AND SOUTH OF CORNER ON LINE WITHIN 5 FT. OF CORNER. POSTED NATIONAL FOREST BOUNDARY LINE EAST AND SOUTH OF CORNER.	RECORD ACCESSORIES FOR ANGLE POINT 8. FROM WHICH, A FORKED ASPEN, 10 INS. DIAM., NOW A FORKED STUMP, 2 FT. ABOVE GROUND, BEARS S. 41° E., 26 LKS. DIST. DIDN'T FIND XBT SCRIBING. A LODGEPOLE PINE, NOW 25 INS. DIAM., BEARS N. 3° W., 134 LKS. DIST., MKD. XBT ON AN OPEN FACE, WITH BLM BT TAG NAILED TO TREE. AN ASPEN, NOW 15 INS. DIAM., BEARS N. 73° W., 27 LKS. DIST., WITH BLM BT TAG NAILED TO TREE. DIDN'T FIND XBT SCRIBING. NO EVIDENCE OF A GRANITE STONE, 12 X 4 X 10 INS., MKD. WITH AN X AND LEFT ON TOP OF BRASS CAP FLUSH WITH THE GROUND. COR. IS LOCATED 9 LKS. W. OF THE CENTER OF A DIRT ROAD CALLED BY DAY DRIVE, BEARS N. 5° E. AND S. 5° W.		THIS SHOWS AN ACTUAL-SIZE DEPICTION OF THE TYPICAL USFS 3-1/4 IN. CAP (WITH SAMPLE MARKINGS) FOR THE BOUNDARY CORNERS SET PER THIS SURVEY. THESE CAPS WERE SET ON A 1/2 IN. DIAMETER, 30 IN. LONG ALUMINUM POST WITH OPEN FLARED END. A PLASTIC-ENCASED 1 IN. DIAMETER MAGNET WAS PLACED AT THE BOTTOM OF THE MONUMENT TO AID IN FUTURE RECOVERY. THE MONUMENTS WERE SET WITH THE TOP OF THE CAP ORIENTED NORTH SUCH THAT IT IS RIGHT-SIDE UP TO A PERSON STANDING SOUTH OF THE MONUMENT FACING NORTH. USFS LAND SURVEY MONUMENT (54-9) AND PROPERTY BOUNDARY (54-2) SIGNS WERE PLACED ON A 1/2 IN. CHANNEL ALUMINUM POST ON THE LINE COMING INTO THE CORNER AS CLOSE AS POSSIBLE TO EACH MONUMENT. THE MONUMENT DESCRIPTION INCLUDES A DEPICTION OF THE CAP MARKINGS THAT IS CORNER SPECIFIC AND A STATEMENT OF WHAT WAS FOUND, IF ANYTHING. BEARING AND DISTANCE TO ACCESSORIES IS NOTED ALONG WITH OTHER PERTINENT INFORMATION. THE BEARING OBSERVED TO EITHER A BEARING TREE OR A BEARING OBJECT ARE TRUE BEARINGS UNLESS OTHERWISE STATED AND ARE DONE WITH A COMPASS WITH THE CORRECT DECLINATION, A TOTAL STATION, OR USING RTK-GPS.	
	FOUND A BLM IRON POST, 2-1/2 INS. DIAM., 6 INS. ABOVE GROUND, WITH BRASS CAP, 3-1/4 INS. DIAM., MKD. AS SHOWN. MONUMENT SURROUNDED BY AN EMBEDDED MOUND OF STONE, 2 FT. DIAM., BASE TO TOP. A STEEL SIGNPOST, BENT AND LEANING AT 45°, IS DRIVEN BEHIND COR. ON FOREST WITH ATTENTION SIGN ATTACHED. NATIONAL FOREST BOUNDARY LINE POSTED NORTH AND WEST OF COR. DROVE AN ALUMINUM SIGNPOST, WITH LAND SURVEY MARKER AND PROPERTY BOUNDARY SIGNS ATTACHED, NEXT TO COR. STRAIGHTENED STEEL SIGNPOST AND SET BEHIND COR.	NEW ACCESSORIES FOR ANGLE POINT 9. FROM WHICH, A BOULDER, MEASURING 4 FT. X 3 FT. X 3 FT., MKD. WITH AN X80, WITH THE X BEARING S. 48° 19' 33" W., 10.3 FT. DIST. A BOULDER, MEASURING 1.5 FT. X 1.5 FT. X 1 FT., MKD. WITH AN X80, WITH THE X BEARING N. 41° 42' 13" W., 12.7 FT. DIST. PAINTED EXPOSED PIPE AND MOUND OF STONE RED. PAINTED RED CIRCLES AROUND X80'S. DIRT ROAD, 0.50 CHS. FROM COR., BEARS E. AND W. AS STATED IN THE FIELD NOTES.			

RECORD OF SURVEY

TRACT 37 IN TOWNSHIP 3 NORTH, RANGE 24 EAST, SECTION 5
AND TRACTS 37 AND 38 IN TOWNSHIP 4 NORTH, RANGE 24 EAST,
IN UNSURVEYED SECTION 32, MT. DIABLO MERIDIAN,
MONO COUNTY, CALIFORNIA

U.S. DEPARTMENT OF AGRICULTURE FOREST SERVICE - REGION 4 HUMBOLDT-TOWNE NATIONAL FOREST 1200 FRANKLIN WAY, SPARKS, NV 89431 775.331.6444 • 775.355.5399 FAX • www.fs.fed.us/r4/htn/		
SURVEYED BY: SJG/HKD/TAP SURVEY DATE: AUG. 2012/MAY 2014	ZONE LEAD CHECK: DFH	DRAWN BY: SJG/EAC CHECKED BY: DFH DATE: MARCH 2015
APPROVED BY:		WILLIAM A. DUNKELBURGER FOREST SUPERVISOR
FILE NAME: CA21_10030NR0240E_S05_201301_TOY		2 SHEET OF 2